# PRODUCT INFORMATION



Automotive Chemicals - Technical Sprays - Cleaning

Version: TS/025

# Valvoline<sup>™</sup> Carburettor Cleaner

High quality cleaner for the interior and the exterior of carburettors and valves, without disassembly.

### **Applications**

Carburettors Valves

#### **Product characteristics**

Directed jet spray
High dissolving properties
Leaves no residue
Non-corrosive
360° valve

#### Directions for use:

Before use, carefully read the directions on the packaging.

Valvoline<sup>™</sup> Carburettor Cleaner should be at room temperature before use. The processing temperature should be between 5 to 30°C. Shake before use.

Switch of the engine and allow to cool down. Remove the air filter. Please refer to the user manual for the location of the air filter.

Spray the exterior of the carburettor until the contamination has disappeared.

Spray the visible parts of the interior of the carburettor and allow to take effect.

Start the engine and let idle with very limited speed. Spray the carburettor cleaner several times at the air inlet and increase the speed of the engine. Switch the engine off and install the air filter.

# PRODUCT INFORMATION



### Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit **www.valvolineeurope.com** 

#### **Typical properties**

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

Valvoline™ Carburettor Cleaner	
Contents	500 ml
Basis	Hydrocarbons
VOC-content	100% w/w
Colour	Transparent
Scent	Characteristic
Relative density at 20°C	0,84 g/ml
Yield	3,0 g/sec
Vapour pressure at 20°C	3 to 4 bar
Flash point active	<21 °C
substance	

This information only applies to products manufactured in the following location(s): Europe

## **Health & Safety**

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet http://sds.valvoline.com

#### Protect the environment

Take used chemicals to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

#### Storage

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces -

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.

<sup>™</sup> Trademark of Valvoline, registered in various countries © 2016